

## Plugs and Receptacles

### Features:

Meets all UL498 requirements

- Heavy gauge steel mounting strap zinc-plated for corrosion resistance.
- For use with copper or aluminum wire, 75°C rated terminals.
- Surface receptacles have patented lay-in terminals and accept up to #4 wire.
- Surface receptacles 3/4" and 1" concentric knockouts and adjustable cord clamp allow for wiring from bottom or back. Made in the U.S.A.

### Power Plugs

Features:

- Meets all UL 498 requirements.
- Furnished with blades for 30 and 59 amp configurations.
- Terminals have pressure plates to protect wires.
- Made in U.S.A.



Part No. 1252



Part No. 0080



Part No. 112BK



Part No. 0021



Part No. 0042

Part No.	Description	Rating	STD/CTN
112BK	3 Pole, 3 Wire Receptacle	50 A-125/250 V	1/10
1252	2 Pole, 3 Wire Receptacle	50 A/250 V	1/10
0021	Plug S21-SP	NMEA14-30 125/250V	1/10
0042	Angle Universal Vinyl 2 Pole, 3 Wire Grounding	50 A/250 V	1/10
0080	Angle Universal Vinyl 3 Pole, 3 Wire Non-Grounding	50-125/250V	1/12