

**Auto-Rewind Hose Reels**

**Standard Series**

Low cost hose storage for compressed air, wash down and welding applications



**Model L8405**  
Designed for use with air tools.



**Model L8435**  
Ideal for high volume air tools.  
Also set-up for water application.

**Air**

Part No.	Description	Hose Size/Length	Hose Material	Max. Working Pressure	Temp. Range (F°)	Reel Inlet Mnpt	Source Hose	Discharge Hose
L8405	Compressed Air	3/8" x 50'	PVC	350 PSI	0° to 140°	3/4" - 11-1/2 (M)	1/4" MNPT	1/4" MNPT
L8435	Air / Water	1/2" x 50'	PVC	350 PSI	0° to 140°*	3/4" - 11-1/2 (M)	3/8"MNPT	1/2" MNPT**

\*40° to 140° for water applications

\*\*3/4"NPTmale garden hose adapter included



**Model L8447**  
For hot wash down applications where maximum water temperature reaches 190°.



**Model L8449**  
Ideal for portable water & general cold wash down applications.

**Water**

Part No.	Description	Hose Size/Length	Hose Material	Max. Working Pressure	Temp. Range (F°)	Reel Inlet Mnpt	Source Hose	Discharge Hose
L8447	Hot Water	5/8" x 50'	EPDM Rubber	200 PSI	40° to 190°	3/4" - 11-1/2 (M)	3/4" - 11-1/2 (F)	3/4" - 11-1/2 (M)
L8449	Cold Water	5/8" x 50'	PVC	150 PSI	40° to 140°	3/4" - 11-1/2 (M)	3/4" - 11-1/2 (F)	3/4" - 11-1/2 (M)



**Models L8463 & L8466**  
Designed for welding & cutting torches.

**Welding**

Part No.	Description	Hose Size/Length	Hose Material	Max. Working Pressure	Temp. Range (F°)	Reel Inlet MUNF	Source Hose	Discharge Hose
L8463	Oxy / Acetylene	1/4" x 50'	Reinforced rubber	200 PSI	N / A	9/16"	9/16" FUNF	9/16" FUNF
L8466	Oxy / Fuel	1/4" x 50'	Reinforced rubber	200 PSI	N / A	9/16"	9/16" FUNF	9/16" FUNF

\*Oxy Fuel is designed for MAPP®, Propane & Natural Gases

## Auto-Rewind Hose Reels

### Levelwind Series-

Retractable hose reels offering efficient cost hose storage for all markets!



**Model L8306**

Designed for use with air tools.



**Model L8335**

Ideal for high volume air tools. Also set-up for water applications.

### Air

Model	Description	Hose Size/Length	Hose Material	Max. Working Pressure	Temp. Range (F°)	Reel Inlet MNPT	Source Hose	Discharge Hose
L8306	Compressed Air	3/8" x 75'	PVC	350 PSI	0° to 140°	3/4" - 11-1/2"	1/4" MNPT	1/4" MNPT
L8335	Air / Water	1/2" x 50'	PVC	350 PSI	0° to 140°*	3/4" - 11-1/2"	1/2" MNPT	1/2" MNPT**

\*40° to 140° for water applications

\*\*3/4"NPTmale garden hose adapter included



**Models L8363 & L8366**

Designed for welding & cutting torches.

### Welding

Model	Description	Hose Size/Length	Hose Material	Max. Working Pressure	Temp. Range (F°)	Reel Inlet MUNF	Source Hose	Discharge Hose
L8363	Oxy / Acetylene	1/4" x 50'	Reinforced rubber	200 PSI	N / A	9/16"	9/16" FUNF	9/16" FUNF
L8366	Oxy / Fuel*	1/4" x 50'	Reinforced rubber	200 PSI	N / A	9/16"	9/16" FUNF	9/16" FUNF

\*Oxy Fuel is designed for MAPP®, Propane & Natural Gases