

## Heaters



### Propane Heaters

#### MH12T

- Variable output of 8, 12 and 14,000 BTU/Hr.
- Hi-Medium-Low Regulator
- Safety shut-off and soft nose P.O.L.
- For direct connection to 4-20 lb. bulk cylinder
- High fire time: 30 hours

#### MH24T

- Variable output of 8, 12, 16, 24 and 28,000 BTU/Hr.
- Hi-Medium-Low Regulator
- Soft Nose P.O.L.
- Run one burner or two
- For direct connection to 20 lb. bulk cylinder
- High fire time: 15 hours (2 burner operation)

#### MH42T

- Variable output of 8, 12, 14, 16, 24, 36 and 42,000 BTU/Hr.
- Three safety shut offs
- Hi-Medium-Low Regulator
- Soft Nose P.O.L.
- Run one, two, or three burners
- For direct connection to 20-100 lb. bulk cylinder
- High fire time: 10 hours



### Forced Air Heaters

- Plug into 120V electrical outlet to operate.
- Hose and regulator included.
- Propane tank not included
- Fully assemble, ready for use
- Made of rugged quality materials 40,000 to 150,000 BTU/Hr. range available in 3 models.
- 6 month warranty

### MH9B Portable Buddy

- Designed and approved for indoor use.
- Automatic low-oxygen shut off system.
- Uses 1 lb. or 20 lb. propane cylinder w/optional hose connection.
- Free standing or wall mount.
- Quiet, odor-free, lightweight, portable.
- Features 15" offset handle so it's easy to carry.
- 4,000 & 9,000 BTU high and low setting
- Heats up to 250 square feet.
- Overall dimensions (L x W x H): 14" x 7" x 14"



- MH40FA** 40,000 BTU/Hr. continuous ignition, 10' LP Hose, 11" WC regulator, AGA & CGA certified.
- MH85FA** 50,000 to 85,000 BTU/Hr. adjustable output continuous ignition, 10' LP hose, 28" WC regulator, AGA & CGA certified
- MH150FA** 150,000 BTU/Hr. Automatic solid state ignition, 10' LP hose, 11" WC regulator, with built-in thermostat, AGA & CGA certified



### MH25LP Garage Heater

- Heats radiantly without heat loss
- No electricity required
- Includes thermostat for individually controlled warmth
- Heats 500-600 sq. ft. (2.5 car garage)
- Easy to operate and install
- Quiet, clean, odor-free operation
- Safe-AGA design certified
- Propane or natural gas
- 22,000 BTU/Hr. Rating
- 30° Normal mounting position
- Reflector dimensions: (L x W x D) 26-1/2" x 11-9/16" x 3-1/4"
- Total dimensions: (L x W x D) 29-3/4" x 12-1/4" x 7"



### MH35LP

- Heats things radiantly, directly. No loss of heat to the air
- Reaches full output in seconds
- No electricity required
- Comes full assembled ready for use
- 35,000 BTU/Hr. rating
- Recommended 20 lb. tank size (not included)
- 12" W x 27" H x 8" D

**Hose Assemblies / Brass Fittings & Accessories**



Part No. F273702



Part No. F273707



Part No. F273717



Part No. F276124



Part No. F276148

**Hose Assemblies**

Part No.	Description	Assembly
F273701	5' Propane	Swivel 1" -20 Male Throwaway Cylinder Thread x P.O.L. with Handwheel
F273702	12' Propane	Swivel 1" -20 Male Throwaway Cylinder Thread x P.O.L. with Handwheel
F273707	5' Propane	1/4" Male Pipe Thread x 3/8" Female Flare
F273717	5' Propane	1/4" Female Pipe Thread x 1/4" Male Pipe Thread
F276124	5' Propane	3/8" Male Pipe Thread x 3/8" Female Pipe Thread
F276148	5' Propane Appliance Extension	9/16" Female Pipe Thread x 9/16" Female Pipe Thread



Part No. F276129

**Brass Fittings**

Part No.	Description
F276129	9/16" Left hand Male Thread x P.O.L.
F276139	1/4" Male Pipe Thread x P.O.L.



Part No. F276136



Part No. F273719

**Replacement Parts**



F273117  
12" Replacement Thermocouple for all Mr. Heaters

**Accessories**

Part No.	Description
F273719	High Pressure Regulator with P.O.L. Range of 0-60 P.S.I.
F276136	P.O.L. x 1/4" Female Pipe Thread Straight Low Pressure Regulator with P.O.L.
	3/8" Female Pipe Thread x P.O.L.